

OVR T2 2L 40-440 P QS



Products Low Voltage Products and Systems Modular DIN Rail Products Surge Protective Devices SPDs
Surge Protective Devices SPD Class II

General Information

Extended Product Type:	OVR T2 2L 40-440 P QS
Product ID:	2CTB803872R5100
EAN:	3660308520623
Catalog Description:	OVR T2 2L 40-440 P QS
Long Description:	B752062

Additional Information

Arrester Class:	II
Auxiliary Circuit Load:	Minimum - Maximum -
Brand / Label:	ABB
Country of Origin:	Bulgaria (BG)
Customs Tariff Number:	85363090
Data Sheet, Technical Information:	-
Declaration of Conformity - CE:	2CTC436004G1701
Discharge Current:	Nominal 20 kA Maximum 40 kA Total 80 kA
EAN:	3660308520623
ETIM 4:	EC000941 - Surge protection device for power supply systems
ETIM 5:	EC000941 - Surge protection device for power supply systems
ETIM 6:	EC000941 - Surge protection device for power supply systems
Impulse Current:	I (imp, 10 / 350 μ s) 2 kA
Invoice Description:	OVR T2 2L 40-440 P QS
Maximum Continuous Operating Voltage (U_c):	(L-PE) 440 V (L-L) 760 V (L-N) - V (N-PE) - V
Minimum Order Quantity:	1 piece
Nominal AC Voltage of the System (U₀):	400 / 690 V
Number of Poles:	2
Number of Protected Poles:	2
Object Classification Code:	141DEC
Options Provided:	Residential, Industry if OVR T1 present upstream
Package Level 1 EAN:	3660308520623
Package Level 1 Gross Weight:	240 g
Package Level 1 Height:	82 mm
Package Level 1 Length:	41 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	117 mm
Preventive Maintenance Feature:	No
Product Main Type:	T2
Product Name:	Surge Protective Devices
Product Net Depth:	58 mm
Product Net Height:	88 mm
Product Net Weight:	240 g

Product Net Weight:	240 g
Product Net Width:	35.6 mm
Product Type:	QS
Selling Unit of Measure:	piece
Short Circuit Withstand Icc:	100 kA
Short Description:	OVR T2 2L 40-440 P QS
Short-Circuit Protective Devices:	Curve B Breakers \leq 125 A Curve C Breakers \leq 125 A gL Type Fuses \leq 125 A gG Type Fuses \leq 125 A
Standards:	IEC 61643-11 / EN 61643-11
Suitable For:	To protect the systems against the transient overvoltage (lightning)
Temporary Overvoltage Test Value (U_T):	581 V
Type of Low Voltage Distribution System:	TN-S IT
UL Certificate:	N
Version:	Plug-in
Voltage Protection Level (U_p):	(L-N) - kV (N-PE) - kV (L-PE) 1.5 kV
Voltage Rating DC:	560 V
Width in Number of Modular Spacings:	2

